

SOT-323 Plastic-Encapsulate Transistor (PNP)


Feature

- Ideally suited for automatic insertion
- Epitaxial planar die construction
- AEC-Q101 qualified
- Complementary to BC817WQ

Mechanical Data

- SOT-323 small outline plastic package
- Epoxy UL: 94V-0
- Mounting position: any

SOT-323



1. BASE
2. EMITTER
3. COLLECTOR

Maximum Ratings & Thermal Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-50	V
Collector-Emitter Voltage	V_{CEO}	-45	V
Emitter -Base Voltage	V_{EBO}	-5	V
Collector Current-Continuous	I_C	-500	mA
Collector Power Dissipation	P_C	200	mW
Junction Temperature	T_j	-55 to +150	$^\circ\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^\circ\text{C}$
Thermal resistance from junction to ambient	$R_{\theta JA}$	625	$^\circ\text{C/W}$

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)







Parameter	Symbol	Test Conditions	Min	Max	Unit
Collector-base breakdown voltage	V_{CBO}	$I_C=-10\mu\text{A}, I_E=0$	-50		V
Collector-emitter breakdown voltage	V_{CEO}	$I_C=-10\text{mA}, I_B=0$	-45		V
Emitter-base breakdown voltage	V_{EBO}	$I_E=-1\mu\text{A}, I_C=0$	-5		V
Collector cut-off current	I_{CBO}	$V_{CB}=-20\text{V}, I_E=0$		-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=-5\text{V}, I_C=0$		-0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=-1\text{V}, I_C=-100\text{mA}$	100	600	
	$h_{FE(2)}$	$V_{CE}=-1\text{V}, I_C=-500\text{mA}$	40		
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=-500\text{mA}, I_B=-50\text{mA}$		-0.7	V
Base-emitter voltage	$V_{BE(on)}$	$V_{CE}=-1\text{V}, I_C=-500\text{mA}$		-1.2	V
Transition frequency	f_T	$V_{CE}=-5\text{V}, I_C=-10\text{mA}$ $f=100\text{MHz}$	80		MHz
Collector output capacitance	C_{ob}	$V_{CB}=-10\text{V}, f=1\text{MHz}$		10	pF



Classification of $h_{FE(1)}$

Rank	BC807-16WQ	BC807-25WQ	BC807-40WQ
Range	100~250	160~400	250~600
Marking	5A	5B	5C






Typical Characteristics






SOT-323 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

SOT-323 Suggested Pad Layout



Notes:

- Controlling dimension: in millimeters.
- General tolerance: $\pm 0.05\text{mm}$.
- The pad layout is for reference purposes only.