

SOT-23 Plastic-Encapsulate Transistor (PNP)


Feature

- Complementary to MMBTA06
- Power Dissipation of 225mW
- High Stability and High Reliability

Mechanical Data

- SOT-23 Small Outline Plastic Package
- Epoxy UL: 94V-0
- Mounting Position: Any

SOT-23



Marking: 2GM

Maximum Ratings & Thermal Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	-80	V
Collector-Emitter Voltage	V_{CEO}	-80	V
Emitter -Base Voltage	V_{EBO}	-4	V
Collector Current-Continuous	I_C	-500	mA
Collector Power Dissipation	P_C	225	mW
Junction Temperature	T_j	150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55-+150	$^{\circ}\text{C}$
Thermal resistance From junction to ambient	$R_{\theta JA}$	555	$^{\circ}\text{C/W}$







Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test Condition	Limit		Unit
			Min	Max	
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=-100\mu\text{A}$, $I_E=0$	-80		V
Collector-emitter breakdown voltage	$V_{(BR)CEO}^*$	$I_C=-1\text{mA}$, $I_B=0$	-80		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=-100\mu\text{A}$, $I_C=0$	-4		V
Collector cut-off current	I_{CBO}	$V_{CB}=-80\text{V}$, $I_E=0$		-100	nA
Emitter cut-off current	I_{EBO}	$V_{EB}=-4\text{V}$, $I_C=0$		-100	nA
Collector cut-off current	I_{CE0}	$V_{CE}=-60\text{V}$, $I_B=0$		-1.0	μA
DC current gain	$h_{FE(1)}^*$	$V_{CE}=-1\text{V}$, $I_C=-10\text{mA}$	100	400	
	$h_{FE(2)}^*$	$V_{CE}=-1\text{V}$, $I_C=-100\text{mA}$	100		
Collector-emitter saturation voltage	$V_{CE(sat)}^*$	$I_C=-100\text{mA}$, $I_B=-10\text{mA}$		-0.25	V
Base -emitter voltage	V_{BE}	$V_{CE}=-1\text{V}$, $I_C=-100\text{mA}$		-1.20	V
Transition frequency	f_T	$V_{CE}=-1\text{V}$, $I_C=-100\text{mA}$, $f=100\text{MHz}$	50		MHz

*Pulse test: pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2.0\%$






Typical Characteristics






SOT-23 Package Dimension



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Notes:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.