



DW07D5-S ESD Protection Diode

Feature

- Uni-directional ESD protection of one line
- 320Watts peak pulse power ($t_p = 8/20\mu s$)
- Working voltage: 7V
- Junction Capacitance: 100pF(Typ)
- Low clamping voltage
- IEC 61000-4-2 $\pm 30kV$ contact $\pm 30kV$ air
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 20A (8/20 μs)


Application

- Handsets and Accessories
- Personal Digital Assestants(PDA's)
- Portable Instrumentation
- Notebooks, Desktops, and Servers
- Digital Cameras


Mechanical Data

- Package: SOD-523
- Molding compound flammability rating: UL 94V-0
- RoHS/WEEE Compliant

Schematic & PIN Configuration



Ordering Information

Part Number	Package	Marking	QTY per Reel	Reel Size
DW07D5-S	SOD-523		5000 pcs	7 inches




Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{PK}	320	W
Peak Pulse Current (8/20 μs)	I_{PP}	20	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	± 30 ± 30	kV
Lead Soldering Temperature	T_L	260 (10seconds)	$^{\circ}\text{C}$
Junction Temperature	T_J	-55 to +125	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-55 to +125	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{RWM}				7.0	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	8.0			V
Reverse Leakage Current	I_R	$V_{RWM}=7.0\text{V}, T=25^{\circ}\text{C}$			0.5	μA
Clamping Voltage	V_C	$I_{PP}=20\text{A}, t_p=8/20\mu\text{s}$		14	16	V
Junction Capacitance	C_j	$V_R = 0\text{V}, f = 1\text{MHz}$		100		pF

Electrical Parameters



Note1: 8/20 μs pulse waveform.



Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure3: Pulse Waveform






Figure 4: Clamping Voltage vs. Ipp





SOD-523 Outline Drawing



COMMON DIMENSION (mm)			
PKG	SOD523		
REF.	MIN.	NOM.	MAX.
A	1.100	1.200	1.300
b	0.250	0.300	0.350
C	1.500	1.600	1.700
D	0.510	0.650	0.770
E	0.700	0.800	0.900
F	0.070	0.140	0.200
L		0.200	