



DWR0504S6L ESD Protection Diode

Feature

- Uni-directional ESD protection of four lines
- 45Watts peak pulse power ($t_p = 8/20\mu s$)
- Working voltage: 5V
- Junction Capacitance: 0.5pF(Typ,between I/O pins)
- Low clamping voltage
- Low leakage current
- IEC 61000-4-2 $\pm 12kV$ contact $\pm 12kV$ air
- IEC 61000-4-5 (Lightning) 3A (8/20 μs)


Application

- USB 2.0 and USB 3.0 Ports
- USB OTG
- Digital Visual Interface (DVI)
- Monitor and Flat Panel Displays
- PCI Express and Serial SATA Ports
- Gigabit Ethernet
- IEEE 1394 Firewire Ports
- Consumer products (STB, DVD, DSC, DVC)


Mechanical Data

- Package: SOT-563
- Molding compound flammability rating: UL 94V-0
- RoHS/WEEE compliant

Dimensions and Pin Configuration



Ordering Information

Part Number	Package	Marking	QTY per Reel	Reel Size
DWR0504S6L	SOT-563		3000 pcs	7 inches



Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise Specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{PK}	45	W
Peak Pulse Current (8/20 μs)	I_{PP}	3	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	± 12 ± 12	kV
Operating Temperature Range	T_J	-55 to +125	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-55 to +150	$^{\circ}\text{C}$


Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise Specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			5	V	Any I/O pin to ground
Breakdown Voltage	V_{BR}	6			V	$I_T = 1\text{mA}$, any I/O pin to ground
Reverse Leakage Current	I_R			0.5	μA	$V_{RWM} = 5\text{V}$, any I/O pin to ground
Clamping Voltage	V_C			12	V	$I_{PP} = 1\text{A}$ (8 x 20 μs pulse), any I/O pin to ground
Clamping Voltage	V_C			15	V	$I_{PP} = 3\text{A}$ (8 x 20 μs pulse), any I/O pin to ground
Junction Capacitance	C_J		0.2	0.4	pF	$V_R = 0\text{V}$, $f = 1\text{MHz}$, between I/O pins
Junction Capacitance	C_J		0.5	0.8	pF	$V_R = 0\text{V}$, $f = 1\text{MHz}$, any I/O pin to ground


Note 1: I/O pins are Pin 1, 3, 4 and 6




Typical Performance Characteristics




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current ($t_p = 8/20\mu$ s)



TLP Measurement



8 X 20 μ s Pulse Waveform




ESD Clamping Voltage

8 kV Contact per IEC61000-4-2



SOT-563 Package Outline Drawing



Suggested Land Pattern

