



DWS03D9CE-Q ESD Protection Diode

Feature

- Bi-directional ESD protection of one line
- 80Watts peak pulse power ($t_p = 8/20\mu s$)
- Working voltage: 3.3V
- Junction Capacitance: 18pF(Typ)
- Low clamping voltage
- Low leakage current
- AEC-Q101 qualified
- IEC 61000-4-2 $\pm 25kV$ contact $\pm 25kV$ air
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 10A (8/20 μs)


Application

- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Pagers Peripherals

Mechanical Data

- Package: SOD-923
- Molding compound flammability rating: UL 94V-0
- RoHS/WEEE Compliant

Schematic & PIN Configuration



Ordering Information

Part Number	Package	Marking	QTY per Reel	Reel Size
DWS03D9CE-Q	SOD-923		8000 pcs	7 inches



Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Units
Peak Pulse Power ($t_p=8/20\mu\text{s}$)	P_{PP}	80	Watts
Peak Pulse Current ($t_p=8/20\mu\text{s}$) (note1)	I_{pp}	10	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	± 25 ± 25	kV
Lead Soldering Temperature	T_L	260 (10seconds)	$^{\circ}\text{C}$
Junction Temperature	T_J	-55 to + 150	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55 to + 150	$^{\circ}\text{C}$


Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{RWM}				3.3	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	3.5			V
Reverse Leakage Current	I_R	$V_{RWM}=3.3\text{V}, T=25^{\circ}\text{C}$			0.5	μA
Clamping Voltage	V_C	$I_{PP}=10\text{A}, t_p=8/20\mu\text{s}$		8		V
Junction Capacitance	C_j	$V_R = 0\text{V}, f = 1\text{MHz}$		18		pF

Electrical Parameters

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current

Note:.. 8/20 μs pulse waveform.





Typical Characteristic

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure3: Pulse Waveform







Figure 4: Clamping Voltage vs. Ipp





SOD-923 Outline Drawing



Dimensions

Symbol	Millimeter		Inches	
	Min	Max	Min	Max
A	0.35	0.43	0.014	0.0172
b	0.15	0.25	0.006	0.010
C	0.07	0.17	0.0028	0.0068
D	0.75	0.85	0.030	0.034
E	0.55	0.65	0.022	0.026
H _E	0.90	1.10	0.036	0.044
L	0.05	0.15	0.002	0.006