



DWS4V5D3CEG ESD Protection Diode

Feature

- Bi-directional ESD protection of one line
- 3000Watts peak pulse power ($t_p = 8/20\mu s$)
- Working voltage: 4.5V
- Junction Capacitance: 425pF(Typ)
- Low clamping voltage
- Low leakage current
- IEC 61000-4-2 $\pm 30kV$ contact $\pm 30kV$ air
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 180A (8/20 μs)


Application

- Power Management System
- Battery Protection
- Personal Digital Assistants(PDA's)
- Portable Instrumentation
- Notebooks ,Desktops ,and Servers

Mechanical Data

- Package: SOD-323
- Molding compound flammability rating: UL 94V-0
- RoHS/WEEE compliant

Schematic & PIN Configuration



Ordering Information

Part Number	Package	Marking	QTY per Reel	Reel Size
DWS4V5D3CEG	SOD-323		3000 pcs	7 inches



Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power ($t_p=8/20\mu\text{s}$)	P_{PP}	3000	Watts
Peak Pulse Current ($t_p=8/20\mu\text{s}$) (note1)	I_{pp}	180	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	± 30 ± 30	kV
Lead Soldering Temperature	T_L	260 (10seconds)	$^{\circ}\text{C}$
Junction Temperature	T_J	-55 to + 125	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55 to + 125	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typical	Max	Unit
Reverse Stand-Off Voltage	V_{RWM}				4.5	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	4.6			V
Reverse Leakage Current	I_R	$V_{RWM}=4.5\text{V}, T=25^{\circ}\text{C}$			1	μA
Clamping Voltage	V_C	$I_{PP}=180\text{A}, t_p=8/20\mu\text{s}$			17	V
Junction Capacitance	C_j	$V_R = 0\text{V}, f = 1\text{MHz}$		425	500	pF

Electrical Parameters

V_{RWM} Reverse Working Voltage Max.


I_R Maximum Reverse Leakage Current @ V_{RWM}

I_T Test Current

V_{BR} Reverse Breakdown Voltage

I_{PP} Maximum Reverse Peak Pulse Current

V_C Clamping Voltage @ I_{PP}





Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure3: Pulse Waveform






Figure 4: Clamping Voltage vs. Ipp





SOD-323 Outline Drawing



Common Dimension				
Symbol	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	1.600	1.800	0.063	0.071
B	0.250	0.350	0.010	0.014
C	2.500	2.700	0.098	0.106
D		1.000		0.039
E	1.200	1.400	0.047	0.055
F	0.080	0.150	0.003	0.006
L	0.475REF		0.019REF	
L1	0.250	0.400	0.010	0.016
H	0.000	0.100	0.000	0.004