

NUP3105LT1G ESD Protection Diode

Feature

- Bi-directional ESD protection of two lines
- 360 Watts peak pulse power ($t_p = 8/20\mu s$)
- Working voltage: 36V
- Junction capacitance: 12pF (Typ)
- Low clamping voltage
- Low leakage current
- AEC-Q101 qualified
- IEC 61000-4-2 $\pm 30kV$ contact $\pm 30kV$ air
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 6A (8/20 μs)


Application

- Portable Electronics
- Set-Top Box
- Cellular Handsets and Accessories
- Control & Monitoring Systems
- RS-232, RS-422 & RS-485


Mechanical Data

- Package: SOT-23
- Molding compound flammability rating: UL 94V-0
- RoHS/WEEE Compliant

Schematic & PIN Configuration



Ordering Information

Part Number	Package	Marking	Packing	Reel Size
NUP3105LT1G	SOT-23		3000 Tape & Reel	7 inches


Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Units
Peak Pulse Power ($t_p=8/20\mu\text{s}$)	P_{PP}	360	Watts
Peak Pulse Current ($t_p=8/20\mu\text{s}$) (note1)	I_{pp}	6	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V_{ESD}	30 30	kV
Lead Soldering Temperature	T_L	260(10seconds)	$^{\circ}\text{C}$
Junction Temperature	T_J	-55 to + 125	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55 to + 125	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{RWM}				36	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	40			V
Reverse Leakage Current	I_R	$V_{RWM}=36\text{V}, T=25^{\circ}\text{C}$		0.1	0.5	μA
Peak Pulse Current	I_{PP}	$t_p=8/20\mu\text{s}$		6		A
Clamping Voltage	V_C	$I_{PP}=6\text{A}, t_p=8/20\mu\text{s}$		54	60	V
Junction Capacitance	C_j	$V_R=0\text{V}, f=1\text{MHz}$ PIN1/PIN2 to PIN3		12	16	pF

Electrical Parameters



Typical Characteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure3: Pulse Waveform






Figure 4: Clamping Voltage vs. Ipp



SOT-23 Outline Drawing



COMMON DIMENSION (mm)			
PKG	SOT23		
REF.	MIN.	NOM.	MAX.
A	0.900		1.150
A2	0.900		1.050
b	0.300		0.500
c	0.080		0.150
D	2.800		3.000
E	1.200		1.400
E1	2.250		2.550
e		0.950	
L		0.550	
L1	0.300		0.500