

20.0A Schottky Barrier Diode



ITO-220AB

Feature

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed
260 °C/10 seconds at terminals

Mechanical Data

- Case : Molded plastic body
- Terminals : Solder plated, solderable per MIL-STD-750,Method 2026
- Polarity : Polarity symbol marking on body
- Mounting Position : Any



Dimensions in millimeters

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	Symbol	MBR 2020FCT	MBR 2040FCT	MBR 2045FCT	MBR 2060FCT	MBR 2065FCT	MBR 20100FCT	MBR 20150FCT	MBR 20200FCT	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	20	40	45	60	65	100	150	200	V
Maximum RMS voltage	V _{RMS}	14	28	31.5	42	45.5	70	105	140	V
Maximum DC blocking voltage	V _{DC}	20	40	45	60	65	100	150	200	V
Maximum average forward rectified current at°Tc=100 C	I _(AV)	20.0								A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	150.0								A
Maximum instantaneous forward voltage per diode at 10.0A	V _F	0.70			0.80		0.85	0.95		v
Maximum DC reverse current at rated DC blocking voltage T _A =25°C T _A =100°C	I _R	0.5 50					0.05 15			mA
Typical thermal resistance	R _{qJC}	4.0								°C/W
Operating junction temperature range	T _J	-55 to +125					-55 to +150			°C
Storage temperature range	T _{STG}	-55 to +150								°C



Ratings and Characteristic Curves

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS





FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS



Ordering Information (Example)

Preferred P/N	Unit Weight(g)	Miniimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
MBR2020FCT~MBR20200FCT	Approximate 1.52	50	1000	5000	Tube